



SILICONI COMMERCIALE SPA

Via Francia 4 Z.I. - 36053 GAMBELLARA (VI) ITALY
Tel +39 0444 649766 Fax +39 0444 440018 www.siliconi.it

Safety Data Sheet ZINCOSIL 400



Safety Data Sheet dated 07/12/2018, version 4.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:
Trade name: ZINCOSIL 400
Trade code: 14510/04

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Paint spray (aerosol).

Uses advised against: Relevant uses are listed above. No other uses are recommended.

1.3. Details of the supplier of the safety data sheet

Company:
SILICONI COMMERCIALE SPA - Via Francia 4 Z.I. 36053 Gambellara (VI) ITALY Phone No.: +39 0444 649766
SILICONI COMMERCIALE SPA - ph n. +39 0444 649766 From Monday to Friday from 8 a.m. to 5 p.m.

Competent person responsible for the safety data sheet:

lab@siliconi.it

1.4. Emergency telephone number

SILICONI COMMERCIALE SPA - ph n. +39 0444 649766 From Monday to Friday from 8 a.m. to 5 p.m.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

Danger, Aerosols 1, Extremely flammable aerosol. Pressurized container: may burst if heated.

Warning, Skin Irrit. 2, Causes skin irritation.

Warning, Eye Irrit. 2, Causes serious eye irritation.

Warning, STOT SE 3, May cause drowsiness or dizziness.

Aquatic Chronic 2, Toxic to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:



Danger

Hazard statements:

H222 Extremely flammable aerosol.

H229 Pressurized container: may burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P271 Use only outdoors or in a well-ventilated area.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

The manufacturer cannot be held responsible in case of damages caused by incorrect use of the product.



SILICONI COMMERCIALE SPA

Via Francia 4 Z.I. - 36053 GAMBELLARA (VI) ITALY
Tel +39 0444 649766 Fax +39 0444 440018 www.siliconi.it

Safety Data Sheet ZINCOSIL 400

Contains

Hydrocarbons, C6, isoalkanes, <5 % n-hexane

Special provisions according to Annex XVII of REACH and subsequent amendments:

Restricted to professional users.

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

Aerosol containers may deform, explode and be thrown far away if exposed to temperature exceeding 50°C. Vapours forms flammable and explosive mixture with air; vapours are heavier than air, so they can accumulate in confined spaces and spread over the ground, causing fire risk even if the ignition occurs far away from the leakage.

Aerosol contains an asphyxiating gas: avoid vapours accumulation in closed spaces because of asphyxiating risk due to the lack of oxygen. High vapour concentration, especially in closed and not proper ventilated spaces, may cause irritation of respiratory tract, nausea, drowsiness or dizziness.

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification
>= 30% - < 40%	Hydrocarbons, C3-4; Petroleum gas	Index number: 649-199-00-1 CAS: 68476-40-4 EC: 270-681-9 REACH No.: 01-2119486557-22	2.5 Press. Gas H280 2.2/1 Flam. Gas 1 H220 DECLK (CLP)*
>= 25% - < 30%	Hydrocarbons, C6, isoalkanes, <5 % n-hexane	EC: 931-254-9 REACH No.: 01-2119484651-34	2.6/2 Flam. Liq. 2 H225 3.10/1 Asp. Tox. 1 H304 3.2/2 Skin Irrit. 2 H315 3.8/3 STOT SE 3 H336 4.1/C2 Aquatic Chronic 2 H411
>= 7% - < 10%	Xylene (reactive mixture of ethylbenzene, m-xylene and p-xylene)	EC: 905-562-9 REACH No.: 01-2119555267-33	2.6/3 Flam. Liq. 3 H226 3.10/1 Asp. Tox. 1 H304 3.1/4/Dermal Acute Tox. 4 H312 3.2/2 Skin Irrit. 2 H315 3.3/2 Eye Irrit. 2 H319 3.1/4/Inhal Acute Tox. 4 H332 3.8/3 STOT SE 3 H335 3.9/2 STOT RE 2 H373 DECLC (CLP)*
>= 5% - < 7%	zinc powder - zinc dust (stabilized)	Index number: 030-002-00-7 CAS: 7440-66-6 EC: 231-175-3 REACH No.: 01-2119467174-37	4.1/A1 Aquatic Acute 1 H400 4.1/C1 Aquatic Chronic 1 H410
>= 0.5% - < 1%	n-butyl acetate	Index number: 607-025-00-1 CAS: 123-86-4 EC: 204-658-1 REACH No.: 01-2119485493-29	2.6/3 Flam. Liq. 3 H226 3.8/3 STOT SE 3 H336 EUH066

DECLK (CLP)*: classification according to Note K (1272/2008 CE Regulation, Annex VI)

DECLC (CLP)*: classification according to Note C (1272/2008 CE Regulation, Annex VI)



SILICONI COMMERCIALE SPA

Via Francia 4 Z.I. - 36053 GAMBELLARA (VI) ITALY
Tel +39 0444 649766 Fax +39 0444 440018 www.siliconi.it

Safety Data Sheet ZINCOSIL 400

For the wording of the listed hazard statements refer to section 16.

XYLENE (REACTIVE MIXTURE OF ETHYLBENZENE, m-XYLENE AND p-XYLENE)

XYLENE - reactive mixture of ethylbenzene, m-xylene and p-xylene:

Xylene, m- CAS 108-38-3 - CE 203-576-3 - INDEX 601-022-00-9 : Conc. % $50 \leq x < 55$

Classification 1272/2008 (CLP): Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Irrit. 2 H315, Note C

Xylene, p- CAS 106-42-3 - CE 203-396-5 - INDEX 601-022-00-9 : Conc. % $15 \leq x < 30$

Classification 1272/2008 (CLP): Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Irrit. 2 H315, Note C

ETHYLBENZENE CAS 100-41-4 - CE 202-849-4 - INDEX 601-023-00-4 : Conc. % $15 \leq x < 30$

Classification 1272/2008 (CLP): Flam. Liq. 2 H225, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373

Xylene, o- CAS 95-47-6 - CE 202-422-2 - INDEX 601-022-00-9 : Conc. % $5 \leq x < 10$

Classification 1272/2008 (CLP): Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Irrit. 2 H315, Note C.

Note: any information in the EC # column starting with number "9" is an EC # Provisional List Number provided by ECHA pending publication of the official European Inventory for substances. Additional information on the CAS number of the substance: Xylene: The following substance is identified by the CAS number both in countries not subject to the REACH Regulations and in the Regulations not yet updated with the new solvent nomenclature: CAS 1330-20-7.

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothes and wash them before reuse.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath). In case of irritation seek medical advice.

In case of eye contact:

After contact with the eyes, rinse immediately with plenty of water with open eyelids for at least 15 minutes. Then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of ingestion:

Aerosol inadvertent ingestion is unlikely to happen. In case of ingestion, consult a doctor. Induce vomiting only in case the doctor suggest to do so. Don't give nothing orally if the person is unconscious.

In case of inhalation:

Move injured people to fresh air and keep them warm and at rest. Consult a doctor in case of difficult breathing.

Protective measurement for first-aiders:

See section 8.2 to check personal protective equipment for first-aid measures.

4.2. Most important symptoms and effects, both acute and delayed

For symptoms and effects due to the contained substances, see Section 11.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None in particular

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: CO₂ (carbon dioxide), dry chemical or chemical foam fire extinguisher.

Extinguishing media which must not be used for safety reasons: Do not use water jets on the burning product.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases. Combustion originates complex gas mixtures, containing carbon monoxide (CO), carbon dioxide (CO₂) and unburned hydrocarbons. Vapours are heavier than air, and may form flammable mixtures with air. Containers may deform and explode if exposed to temperature exceeding 50 °C.

5.3. Advice for firefighters

Wear full fire protection equipment (Type EN 11611 or EN469) with self-contained breathing apparatus (Type EN 137), visor helmet and neck protection (Type EN443), anti-heat gloves (Type EN407).

Collect contaminated fire extinguishing water separately. Fire extinguishing water must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

Nebulised water can be used to cool down overheated containers after their exposure to fire. Prevent extinguishing media from entering the sewage or watercourses.



SILICONI COMMERCIALE SPA

Via Francia 4 Z.I. - 36053 GAMBELLARA (VI) ITALY
Tel +39 0444 649766 Fax +39 0444 440018 www.siliconi.it

Safety Data Sheet ZINCOSIL 400

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For those who do not intervene directly:

Eliminate all sources of ignition (cigarettes, flames, sparks, electricity, etc.) or heat from the area in which the leak occurred and provide adequate ventilation.

Evacuate the surrounding areas and prevent the entry of external and unprotected personnel.

Notify emergency teams.

Block the loss if there is no danger.

Do not handle damaged containers or leaked product without first wearing appropriate protective equipment.

Avoid breathing vapors or mist.

For information on risks to the environment and health, respiratory protection, ventilation and individual protection measures, refer to section 8.

For those who intervene directly:

Emergency operators are recommended to wear suitable personal protective equipment as described in section 8.

The vapours are heavier than the air and, in case of spills, can accumulate in enclosed spaces and in low areas where it can ignite easily.

In the event that the situation cannot be fully assessed or if there is a risk of oxygen deficiency, use only an autonomous respirator (Type EN137).

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Provide proper ventilation. Use non-sparking tools and equipment. Wash with plenty of water. Contain spillage with non-combustible absorbing materials such as sand, earth, vermiculite, diatomaceous earth and dispose of the product by means of a waste disposal authorized company.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Pressurized container. Do not perforate or burn even after use.

Do not use near flames or other possible sources of ignition. Do not smoke during work.

Avoid accumulation of electrostatic charge. Do not spray on flames, warm surface or incandescent objects.

Use only in a well ventilated area.

Vapours may burn, causing explosions. Prevent vapours accumulation by keeping doors and windows open and by assuring a proper ventilation.

Vapours are heavier than air, so they can accumulate in confined spaces and spread over the ground, causing fire risk even if the ignition occurs far away from the leakage.

Avoid direct exposure to sunlight.

Do not expose to temperatures exceeding 50°C/122°F.

Avoid skin and eye contact, vapours and mist inhalation.

Environmental protection measures:

Reduce the risk of releasing the mixture in the environment/air. Avoid inadvertent leakage, store far away from sewer.

Occupational hygiene measures:

Contaminated clothes have to be substituted before entering dining rooms.

Do not eat, drink or smoke at workplace.

Wash hands after using the mixture.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions:

Store in a well ventilated area, protect from direct sunlight.

Recommended storage temperature: between 15°C and 30°C.

Protect from flames, sparks, heat/combustion sources.

Keep containers in an upright and safe position, preventing them from falls and collisions.

Do not store in corridors and stairs.

Store only in original and tightly closes containers.

Do not perforate or open the containers.

Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.



SILICONI COMMERCIALE SPA

Via Francia 4 Z.I. - 36053 GAMBELLARA (VI) ITALY
Tel +39 0444 649766 Fax +39 0444 440018 www.siliconi.it

Safety Data Sheet

ZINCOSIL 400

Incompatible materials:

Do not store with combustibles, self-flammable or self-heating substances, organic peroxides, oxidising agents, pyrophoric solids or liquids, explosives.

See also section 10.

Instructions as regards storage premises:

Proper ventilation. Avoid electrostatic charge accumulation.

Storage class:

See section 15.1 (Seveso III).

7.3. Specific end use(s)

See section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Hydrocarbons, C3-4; Petroleum gas - CAS: 68476-40-4

TLV TWA - 1000 ppm (2400mg/m³)

TLV STEL - 4000 ppm (9600mg/m³)

Hydrocarbons, C6, isoalkanes, <5 % n-hexane

TLV TWA - 1200 mg/m³

Xylene (reactive mixture of ethylbenzene, m-xylene and p-xylene)

TLV-ACGIH - TWA(8h): 434 mg/m³, 100 ppm - STEL(15min): 651 mg/m³, 150 ppm

n-butyl acetate - CAS: 123-86-4

ACGIH - TWA(8h): 50 ppm - STEL: 150 ppm - Notes: Eye and URT irr

DNEL Exposure Limit Values

Hydrocarbons, C3-4; Petroleum gas - CAS: 68476-40-4

Worker Industry: 2.21 19141.03 - Consumer: 0.0664 19141.03 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Industry: 23.4 mg/Kg bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Hydrocarbons, C6, isoalkanes, <5 % n-hexane

Consumer: 1301 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects - Notes: bw/day

Worker Industry: 13964 19141.03 - Consumer: 1377 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects - Notes: bw/day

Worker Industry: 5306 19141.03 - Consumer: 1137 19141.03 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects - Notes: bw/day

Xylene (reactive mixture of ethylbenzene, m-xylene and p-xylene)

Worker Industry: 221 mg/m³ - Consumer: 65.3 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Industry: 442 mg/m³ - Consumer: 260 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term (acute)

Worker Industry: 221 mg/m³ - Consumer: 65.3 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects

Worker Industry: 442 mg/m³ - Consumer: 260 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Industry: 212 mg/Kg bw/day - Consumer: 125 mg/Kg bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

xylene (reaction mass of ethylbenzene and m-xylene and p-xylene)

Target: Fresh Water - Value: 0.327 mg/l

Target: Marine water - Value: 0.327 mg/l

Target: Freshwater sediments - Value: 12.46 mg/kg

Target: Marine water sediments - Value: 12.46 mg/kg

Target: Soil (agricultural) - Value: 2.31 mg/kg

8.2. Exposure controls

Appropriate engineering controls:

Adequately ventilate rooms where the product is stored and handled. Use only if the place is adequately ventilated. Local ventilation might be necessary for certain operations. Minimize exposure concentration at the workplace. Use proper technical equipment to maintain the concentration below threshold limit values or guidelines for exposure.

Eye protection:

Wear goggles with lateral protection EN166 .

If exposure to vapours cause a sense of bother to eyes, use antigas mask with complete facial.

Protection for skin:

Wear clean antistatic and covering garments, and antistatic safety-shoes for professional use, S2 category (Type EN20345).



SILICONI COMMERCIALE SPA

Via Francia 4 Z.I. - 36053 GAMBELLARA (VI) ITALY
Tel +39 0444 649766 Fax +39 0444 440018 www.siliconi.it

Safety Data Sheet

ZINCOSIL 400

In case of long and frequent contact use protective garments, than are impervious to this product (Type EN340 – EN13034).

Protection for hands:

During manipulation is necessary protect hands with chemical resistant gloves Type EN374 (PVC, PE, neoprene, Nitrile, Viton, not natural Rubber). It is recommended to use gloves with Protective Index 6: permeation time >480min, Thickness >0,3mm. Change gloves in case of wear, cracks or internal contamination.

Respiratory protection:

Product concentration in air should be lower than exposure limit values. As the concentration exceed the threshold limit values, proper respiratory protection should be used. Use protective masks EN149 with FFP2 filters, half-face respirator type EN140 with EN143:A2 filters, or full face breathing mask EN136 with EN143:A2 filters.

Thermal Hazards:

The aerosol container if overheated, deforms, breaks and it can be thrown a considerable distance.

Environmental exposure controls:

Emissions originating from production and use of the product, included those originated during ventilation operations, should be monitored in order to comply with the environmental protection regulations. Product residuals shouldn't be drained into watercourses or waste water.

For further information see section 6.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:
Appearance and colour:	Pressurized container with liquefied gas	--
Odour:	Characteristic	--
Odour threshold:	N.A.	--
pH:	N.A.	--
Melting point / freezing point:	N.A.	--
Initial boiling point and boiling range:	> -42 °C	--
Flash point:	< 0 °C	--
Evaporation rate:	N.A.	--
Solid/gas flammability:	N.A.	--
Upper/lower flammability or explosive limits:	15 Vol % - 1.8 Vol %	--
Vapour pressure:	N.A.	--
Vapour density:	> 2	--
Relative density:	N.A.	--
Solubility in water:	insoluble	--
Solubility in oil:	soluble	--
Partition coefficient (n-octanol/water):	N.A.	--
Auto-ignition temperature:	> 300 °C	--
Decomposition temperature:	N.A.	--
Viscosity:	N.A.	--
Explosive properties:	Non explosive	--
Oxidizing properties:	N.A.	--

9.2. Other information

Properties	Value	Method:
Miscibility:	N.A.	--
Fat Solubility:	N.A.	--
Conductivity:	N.A.	--
Substance Groups relevant properties	N.A.	--

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

No hazardous reaction are expected under normal use conditions.

10.2. Chemical stability

Pressurized container.

Do not perforate nor burn, even after use. Protect from direct sunlight.

Do not expose to temperature exceeding 50°C/122°F.

Refer to section 7 for information regarding handling and storage.



SILICONI COMMERCIALE SPA

Via Francia 4 Z.I. - 36053 GAMBELLARA (VI) ITALY
Tel +39 0444 649766 Fax +39 0444 440018 www.siliconi.it

Safety Data Sheet

ZINCOSIL 400

- 10.3. Possibility of hazardous reactions
No hazardous reaction are expected under normal use conditions.
Vapours may form explosive mixtures with air.
Aerosol containers may deform, explode and be thrown far away if exposed to temperature exceeding 50°C.
- 10.4. Conditions to avoid
Avoid exposure to sunlight. Avoid overheating and temperatures >50°C. Keep away from oxidizing agents.
- 10.5. Incompatible materials
Avoid contact with combustible materials. The product could catch fire.
Avoid strong reducing and oxidising agents, strong acid and alkalis, warm object/materials.
- 10.6. Hazardous decomposition products
The product doesn't decompose under normal conditions. See section 5 for thermal decomposition.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological information of the product:

ZINCOSIL 400

- a) acute toxicity
Not classified
Based on available data, the classification criteria are not met
- b) skin corrosion/irritation
The product is classified: Skin Irrit. 2 H315
- c) serious eye damage/irritation
The product is classified: Eye Irrit. 2 H319
- d) respiratory or skin sensitisation
Not classified
Based on available data, the classification criteria are not met
- e) germ cell mutagenicity
Not classified
Based on available data, the classification criteria are not met
- f) carcinogenicity
Not classified
Based on available data, the classification criteria are not met
- g) reproductive toxicity
Not classified
Based on available data, the classification criteria are not met
- h) STOT-single exposure
The product is classified: STOT SE 3 H336
- i) STOT-repeated exposure
Not classified
Based on available data, the classification criteria are not met
- j) aspiration hazard
Not classified
Based on available data, the classification criteria are not met

Toxicological information of the main substances found in the product:

Hydrocarbons, C6, isoalkanes, <5 % n-hexane

- a) acute toxicity:
Test: LC50 - Route: Inhalation - Species: Rat > 20 mg/l - Duration: 4h
Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg
Test: LD50 - Route: Skin - Species: Rabbit > 3000 mg/kg
xylene (reaction mass of ethylbenzene and m-xylene and p-xylene)
- a) acute toxicity:
Test: LD50 - Route: Oral - Species: Rat 3523 mg/kg
Test: LC50 - Route: Inhalation - Species: Rat 6350 Ppm
Test: LD50 - Route: Skin - Species: Rabbit 12126 mg/kg
- b) skin corrosion/irritation:
Species: Rabbit Slightly Irritant
- c) serious eye damage/irritation:
Species: Rabbit Not corrosive
- zinc powder - zinc dust (stabilized) - CAS: 7440-66-6
- a) acute toxicity:
Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg
Test: LC50 - Route: Inhalation - Species: Rat > 5.4 mg/l - Duration: 4h



SILICONI COMMERCIALE SPA

Via Francia 4 Z.I. - 36053 GAMBELLARA (VI) ITALY
Tel +39 0444 649766 Fax +39 0444 440018 www.siliconi.it

Safety Data Sheet

ZINCOSIL 400

n-butyl acetate - CAS: 123-86-4

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 6400 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 21.1 mg/l - Duration: 4h

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

ZINCOSIL 400

The product is classified: Aquatic Chronic 2 - H411

Hydrocarbons, C6, isoalkanes, <5 % n-hexane

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 1 mg/l - Duration h: 48 - Notes: Oryzia latipes - Dati di materiali simili

Endpoint: LC50 - Species: Daphnia = 3.87 mg/l - Duration h: 48 - Notes: Daphnia Magna - Dati di materiali simili

Endpoint: SC2 - Species: Algae = 55 mg/l - Duration h: 72 - Notes: Pseudokirchneriella subcapitata - Dati di materiali simili

Endpoint: NOEC - Species: Algae = 30 mg/l - Duration h: 72 - Notes: Pseudokirchneriella subcapitata - Dati di materiali simili

xylene (reaction mass of ethylbenzene and m-xylene and p-xylene)

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish 2.6 mg/l - Duration h: 96 - Notes: p-xylene

Endpoint: EC50 - Species: Daphnia magna 1 mg/l - Duration h: 24 - Notes: o-xylene

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Fish > 1.3 mg/l - Notes: mix-xylene

Endpoint: NOEC - Species: Daphnia magna 0.96 mg/l - Notes: 7 day - ethylbenzene

zinc powder - zinc dust (stabilized) - CAS: 7440-66-6

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 7.1 mg/l - Duration h: 96 - Notes: Nothobranchius guentheri

Endpoint: EC50 - Species: Daphnia = 2.8 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 0.15 mg/l - Duration h: 72 - Notes: Pseudokirchneriella subcapitata

12.2. Persistence and degradability

None

Hydrocarbons, C6, isoalkanes, <5 % n-hexane

Biodegradability: Readily biodegradable - Test: N.A. - Duration: N.A. - %: N.A. - Notes: N.A.

xylene (reaction mass of ethylbenzene and m-xylene and p-xylene)

Biodegradability: Readily biodegradable

12.3. Bioaccumulative potential

xylene (reaction mass of ethylbenzene and m-xylene and p-xylene)

Test: BCF - Bioconcentration factor 25.9 - Notes: (aquatic species)

n-butyl acetate - CAS: 123-86-4

Bioaccumulation: N.A. Test: Kow - Partition coefficient 2.3 - Duration: N.A. - Notes: N.A.

Bioaccumulation: N.A. Test: Partition coefficient soil/water 0-3 - Duration: N.A. - Notes: N.A.

Bioaccumulation: N.A. Test: BCF - Bioconcentration factor 15.3 - Duration: N.A. - Notes: N.A.

12.4. Mobility in soil

xylene (reaction mass of ethylbenzene and m-xylene and p-xylene)

Test: Koc 537 - Notes: (20 °C) of o-xylene

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

None

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible.

Send to authorised disposal plants or for incineration under controlled conditions.

In so doing, comply with the local and national regulations currently in force.

Containers may explode if exposed to temperature exceeding 50°C, even if they contain only product residual.

Empty containers shouldn't be dispersed in the environment.

European Waste Catalogue (EWC):

Domestic uses: aerosol wastes originating from domestic use are not included in this regulation.



SILICONI COMMERCIALE SPA

Via Francia 4 Z.I. - 36053 GAMBELLARA (VI) ITALY
Tel +39 0444 649766 Fax +39 0444 440018 www.siliconi.it

Safety Data Sheet ZINCOSIL 400

Industrial uses: aerosol waste is classified as 'Packaging containing residues of, or contaminated by, dangerous substances', EWC code 15.01.10.

SECTION 14: Transport information

- 14.1. UN number
ADR-UN number: 1950
IATA-Un number: 1950
IMDG-Un number: 1950
- 14.2. UN proper shipping name
ADR-Shipping Name: AEROSOLS, Flammable Limited Quantity: max 1000ml Total gross mass of package not exceed 30 kg LQ2
IATA-Technical name: AEROSOLS
IMDG-Technical name: AEROSOLS, Flammable Limited Quantity: max 1000ml Total gross mass of package not exceed 30 kg LQ2
- 14.3. Transport hazard class(es)
ADR-Class: 2,5F
ADR-Label: 2.1
IATA-Class: 2
IATA-Label: 2.1
IMDG-Class: 2
- 14.4. Packing group Not applicable for Limited Quantity
- 14.5. Environmental hazards
Marine pollutant: Marine pollutant
- 14.6. Special precautions for user
IMDG-Technical name: AEROSOLS, Flammable Limited Quantity: max 1000ml Total gross mass of package not exceed 30 kg LQ2
IMDG-EMS: F-D
IMDG-MFAG: S-U
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code
N.A.

SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
Dir. 98/24/EC (Risks related to chemical agents at work)
Dir. 2000/39/EC (Occupational exposure limit values)
Regulation (EC) n. 1907/2006 (REACH)
Regulation (EC) n. 1272/2008 (CLP)
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
Regulation (EU) 2015/830
Regulation (EU) n. 286/2011 (ATP 2 CLP)
Regulation (EU) n. 618/2012 (ATP 3 CLP)
Regulation (EU) n. 487/2013 (ATP 4 CLP)
Regulation (EU) n. 944/2013 (ATP 5 CLP)
Regulation (EU) n. 605/2014 (ATP 6 CLP)
Regulation (EU) n. 2015/1221 (ATP 7 CLP)
Regulation (EU) n. 2016/918 (ATP 8 CLP)
Regulation (EU) n. 2016/1179 (ATP 9 CLP)
Regulation (EU) n. 2017/776 (ATP 10 CLP)
- Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:
None
- Where applicable, refer to the following regulatory provisions :
Directive 2012/18/EU (Seveso III)
Regulation (EC) nr 648/2004 (detergents).
Dir. 2004/42/EC (VOC directive)
- Provisions related to directive EU 2012/18 (Seveso III):
Seveso III category according to Annex 1, part 1
Product belongs to category: P3a, E2
- 15.2. Chemical safety assessment
No Chemical Safety Assessment has been carried out for the mixture.



SILICONI COMMERCIALE SPA

Via Francia 4 Z.I. - 36053 GAMBELLARA (VI) ITALY
Tel +39 0444 649766 Fax +39 0444 440018 www.siliconi.it

Safety Data Sheet ZINCOSIL 400

SECTION 16: Other information

Full text of phrases referred to in Section 3:

- H280 Contains gas under pressure; may explode if heated.
- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- H226 Flammable liquid and vapour.
- H312 Harmful in contact with skin.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

Hazard class and hazard category	Code	Description
Flam. Gas 1	2.2/1	Flammable gas, Category 1
Aerosols 1	2.3/1	Aerosol, Category 1
Press. Gas	2.5	Gases under pressure
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
Acute Tox. 4	3.1/4/Dermal	Acute toxicity (dermal), Category 4
Acute Tox. 4	3.1/4/Inhal	Acute toxicity (inhalation), Category 4
Asp. Tox. 1	3.10/1	Aspiration hazard, Category 1
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3
STOT RE 2	3.9/2	Specific target organ toxicity - repeated exposure, Category 2
Aquatic Acute 1	4.1/A1	Acute aquatic hazard, category 1
Aquatic Chronic 1	4.1/C1	Chronic (long term) aquatic hazard, category 1

Paragraphs modified from the previous revision:

- SECTION 1: Identification of the substance/mixture and of the company/undertaking
- SECTION 2: Hazards identification
- SECTION 3: Composition/information on ingredients
- SECTION 4: First aid measures
- SECTION 5: Firefighting measures
- SECTION 6: Accidental release measures
- SECTION 7: Handling and storage
- SECTION 8: Exposure controls/personal protection
- SECTION 9: Physical and chemical properties
- SECTION 10: Stability and reactivity
- SECTION 11: Toxicological information
- SECTION 12: Ecological information
- SECTION 13: Disposal considerations
- SECTION 14: Transport information
- SECTION 15: Regulatory information
- SECTION 16: Other information

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Aerosols 1, H222+H229	On basis of test data



SILICONI COMMERCIALE SPA

Via Francia 4 Z.I. - 36053 GAMBELLARA (VI) ITALY
Tel +39 0444 649766 Fax +39 0444 440018 www.siliconi.it

Safety Data Sheet ZINCOSIL 400

Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
STOT SE 3, H336	Calculation method
Aquatic Chronic 2, H411	Calculation method

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities
SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information herein contained is based on our state of knowledge at the above-specified date. It refers solely to the indicated product and constitutes no guarantee of peculiar qualities.

It is responsibility of the user to make sure of the accuracy and the completeness of the information with respect to the specific intended use.

This MSDS cancels and replaces any previous release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
N.A.:	Not available
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.